



WELDING PROCEDURE DATA SHEET (WPDS)				WPDS No.: FCAW - PLUG1																																																																																						
RC Technical Services 512 MacDougall Road MacDougall Settlement, N.B.				Rev: 0																																																																																						
				Date: July 28, 2019																																																																																						
				Ref. WPS: FCAW-CS																																																																																						
				Ref. Standards: CSA W47.1, CSA W59																																																																																						
				Prequalified joint no.: CSA W47.1 Clause 11.2.2. b) ii																																																																																						
Base Metal: CSA W59, Table 11.1, GROUPS 1, 2, 3				Filler Metal / Classification CSA W48: E491T-9-H8 AWS A5.20: E71T-9-H8																																																																																						
Thickness: SEE SKETCH				FCAW																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 20%;">Shielding:</td><td>100% CO2</td></tr> <tr><td>Gas Flow Rate:</td><td>30 - 40 CFH</td></tr> <tr><td>Metal Transfer Mode:</td><td>SPRAY</td></tr> <tr><td>Process Mode:</td><td>SEMI-AUTOMATIC</td></tr> <tr><td>Position:</td><td>FLAT</td></tr> <tr><td>Joint Type:</td><td>TEE</td></tr> <tr><td>Weld Type:</td><td>PLUG</td></tr> <tr><td>Penetration:</td><td>PARTIAL</td></tr> <tr><td>Electrode Stickout:</td><td>1/2" to 3/4"</td></tr> <tr><td>Effective Area:</td><td>AREA OF HOLE</td></tr> <tr><td>Preheating Temp.</td><td>10°C & Table 5.3 W59</td></tr> <tr><td>Interpass Temp.:</td><td>260°C (500°F) MAX</td></tr> <tr><td>Backgouging Method:</td><td>N/A</td></tr> <tr><td>Backgouging Depth:</td><td>N/A</td></tr> <tr><td>Backing Material:</td><td>See base metal above</td></tr> <tr><td>Backing Thickness:</td><td>SEE SKETCH</td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> <tr><td> </td><td> </td></tr> </table>				Shielding:	100% CO2	Gas Flow Rate:	30 - 40 CFH	Metal Transfer Mode:	SPRAY	Process Mode:	SEMI-AUTOMATIC	Position:	FLAT	Joint Type:	TEE	Weld Type:	PLUG	Penetration:	PARTIAL	Electrode Stickout:	1/2" to 3/4"	Effective Area:	AREA OF HOLE	Preheating Temp.	10°C & Table 5.3 W59	Interpass Temp.:	260°C (500°F) MAX	Backgouging Method:	N/A	Backgouging Depth:	N/A	Backing Material:	See base metal above	Backing Thickness:	SEE SKETCH																	<div style="text-align: center;">  <p>Weld Technique</p> </div> <div style="text-align: center; margin-top: 20px;">  <p>Hole diameter = 21mm (13/16") Ladder rung diameter = 19mm (3/4") Fill thickness = 5mm (3/16")</p> </div> <p style="margin-top: 20px;">Weld technique: Continuous pass shall be deposited around the root of the joint and then deposited along a spiral path to the center of the hole. If the arc is broken or the slag is allowed to cool, remove the slag completely before restarting the weld.</p>																																						
Shielding:	100% CO2																																																																																									
Gas Flow Rate:	30 - 40 CFH																																																																																									
Metal Transfer Mode:	SPRAY																																																																																									
Process Mode:	SEMI-AUTOMATIC																																																																																									
Position:	FLAT																																																																																									
Joint Type:	TEE																																																																																									
Weld Type:	PLUG																																																																																									
Penetration:	PARTIAL																																																																																									
Electrode Stickout:	1/2" to 3/4"																																																																																									
Effective Area:	AREA OF HOLE																																																																																									
Preheating Temp.	10°C & Table 5.3 W59																																																																																									
Interpass Temp.:	260°C (500°F) MAX																																																																																									
Backgouging Method:	N/A																																																																																									
Backgouging Depth:	N/A																																																																																									
Backing Material:	See base metal above																																																																																									
Backing Thickness:	SEE SKETCH																																																																																									
Welding Parameters: <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Fill Thickness mm in</th> <th>Side</th> <th>Layer</th> <th>Pass</th> <th>Electrode Diameter inch</th> <th>Current Polarity</th> <th>Amperes (+/-10%)</th> <th>WFS inch / min. (+/-10%)</th> <th>Volts (+/-7%)</th> <th>Arc Travel in/min (+/-15%)</th> </tr> </thead> <tbody> <tr> <td>5 3/16</td> <td>I</td> <td>1</td> <td>1</td> <td>1/16</td> <td>DCRP</td> <td>325</td> <td>300</td> <td>27</td> <td>20</td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>											Fill Thickness mm in	Side	Layer	Pass	Electrode Diameter inch	Current Polarity	Amperes (+/-10%)	WFS inch / min. (+/-10%)	Volts (+/-7%)	Arc Travel in/min (+/-15%)	5 3/16	I	1	1	1/16	DCRP	325	300	27	20																																																												
Fill Thickness mm in	Side	Layer	Pass	Electrode Diameter inch	Current Polarity	Amperes (+/-10%)	WFS inch / min. (+/-10%)	Volts (+/-7%)	Arc Travel in/min (+/-15%)																																																																																	
5 3/16	I	1	1	1/16	DCRP	325	300	27	20																																																																																	
Remarks: <div style="height: 150px; border: 1px solid black;"></div>				CWB Approval: <div style="height: 150px; border: 1px solid black;"></div>			Company's Approval: <div style="height: 150px; border: 1px solid black;"></div>																																																																																			