



PREMIUM QUALITY
Replacement Torch Tips




**PROSTAR™
Replacement
Torch Tips**

Manufactured to meet the most rigid requirements of the metal fabrication industry, PROSTAR™ replacement tips are designed to fit the majority of the gas equipment manufacturers' styles (Airco®, Harris®, Oxweld®, Purox®, Smith® and Victor®), for use in many common and special applications.



Airco Styles	Sizes	Gas*	Application
144 (1-pc)	0 – 4	A	General
164 (1-pc)	00 – 4	A	Heavy Preheat
263 (2-pc)	0 – 2	P	General

Airco Tip Selection Chart					
Size	Cutting Capacity	Size	Cutting Capacity	Size	Cutting Capacity
00	1/8" (3 mm)	1	1/2" (13mm)	3	2" (51 mm)
0	1/4" (6 mm)	2	1" (25 mm)	4	2 1/2" (64 mm)



Harris Styles	Sizes	Gas*	Application
6290 (1-pc)	00 – 4	A	General
6290NX (2-pc)	0 – 2	P	General

Harris Tip Selection Chart					
Size	Cutting Capacity	Size	Cutting Capacity	Size	Cutting Capacity
00	3/8" (10 mm)	1	1" (25 mm)	3	3" (76 mm)
0	5/8" (16 mm)	2	2" (51 mm)	4	6" (152 mm)




Oxweld Styles	Sizes	Gas*	Application
1502 (1-pc)	2 – 10	A	General
1515 (1-pc)	4 – 12	P	Heavy Preheat

Oxweld Tip Selection Chart					
Size	Cutting Capacity	Size	Cutting Capacity	Size	Cutting Capacity
2	1/8" (3 mm)	4	5/8" (16 mm)	10	10" (254 mm)
3	3/8" (10 mm)	6	1 1/2" (38 mm)	12	12" (305 mm)
		8	5" (127 mm)		



Purox Styles	Sizes	Gas*	Application
4202 (1-pc)	3 – 11	A	General
4203 (2-pc)	3, 5	P	General

Purox Tip Selection Chart					
Size	Cutting Capacity	Size	Cutting Capacity	Size	Cutting Capacity
3	1/4" (6 mm)	5	1 1/2" (38 mm)	9	6" (152 mm)
4	5/8" (16 mm)	7	4" (102 mm)	11	10" (254 mm)



Smith Styles	Sizes	Gas*	Application
MC-12 (1-pc)	0 – 3	A	General
SC-12 (1-pc)	1, 2	A	General
MCP (2-pc)	0, 1	P	General
SC50A (2-pc)	1, 2	P	General

Smith Tip Selection Chart					
Size	Cutting Capacity	Size	Cutting Capacity	Size	Cutting Capacity
0	3/8" (10 mm)	2	1 1/4" (32 mm)		
1	5/8" (16 mm)	3	2" (51 mm)		



Victor Styles	Sizes	Gas*	Application
1-101 (1-pc)	00 – 4	A	General
3-101 (1-pc)	00 – 2	A	General
GPN (2-pc)	0 – 2	P	General
3-GPN (2-pc)	0, 1	P	General

Victor Tip Selection Chart					
Size	Cutting Capacity	Size	Cutting Capacity	Size	Cutting Capacity
00	1/4" (6 mm)	2	1" (25 mm)		
0	1/2" (13mm)	3	2" (51 mm)		
1	3/4" (19 mm)	4	3" (76 mm)		

* A – Acetylene P – Propane

Get to know the complete PROSTAR line of premium quality products for your welding, heating and cutting operations – flashback arrestors, reverse flow check valves, welding hose, lenses and goggles, leather protective clothing and other accessories.



The information contained herein is offered for use by technically qualified personnel at their discretion and risk. All statements, technical information, and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto.

Prostar and Praxair are trademarks of Praxair Technology, Inc.
© 1997 Praxair Technology, Inc.

Praxair Distribution, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113

PROSTAR products are available through
Praxair's retail stores.

P-8142 10M 04/97 Printed in USA